Ancillary Base Sounder



Product	
Product	Ancillary Base Sounder
Part No.	45681-276
Digital communication	XP95, Discovery and CoreProtocol® compatible

Compliance CE SBSC SBSC PRODUKT FG

Product

The Ancillary Base Sounder is a local-area sounder designed for indoor use with XP95,Discovery or Soteria detectors and control panels using the appropriate software.

The sounder incorporates a base into which an XP95, Discovery or Soteria detector can be fitted. Power is provided by the control panel via the loop wiring to which it is connected.

With a guaranteed sound output of $85 \, dB(A)$ at one metre the device has a current consumption of 3 mA. This means that a very low current noise is generated on the loop and means that up to $126 \, sounders$ can be connected to the loop.

- Sound output of 85 dB(A) at one metre
- · Current consumption of only 3 mA
- · Loop-powered
- Responds to signals from the associated detector does not have an address of its own
- · Adjustable volume control

Technical data

All data is supplied subject to change without notice. Specifications are typical at 24 V, 25°C and 50% RH unless otherwise stated

Operating voltage 17 V dc - 28 V dc

Current consumption at 24 V

Quiescent < 100 μ A Sounder operated 3 mA Sounder pressure level at 1 m 85 dB(A)

Frequency 990 Hz for 0.5 s, 630 Hz for 0.5 s

Operating temperature -20 °C to +60 °C

Humidity (no condensation) 0 - 95% RH

IP Rating IP23D

Standards & approvals CPR, VNIIPO, SBSC, FG

Dimensions 115 mm diameter x 38 mm height

Weight 140 g

Materials Housing: White flame-retardant

polycarbonate

Terminals: Nickel plated stainless

steel

Tone frequency and volume control

The sounder produces an uninterrupted alternating tone of 990 Hz for 0.5 seconds and 630 Hz for 0.5 seconds. Volume is adjustable steplessly from 70 dB(A) to 85 dB(A). However, the sounder does not have a synchronisation feature or pulsed tone.

The sounder responds to signals from the associated detector or beacon and does not have an address of its own.

EMC Directive 2014/30/EU

The Ancillary Base Sounder complies with the essential requirements of the EMC Directive 2014/30/EU, provided that it is used as described in this data sheet.

A copy of the Declaration of Conformity is available from the Apollo website: www.apollo-fire.co.uk

Conformity of the Ancillary Base Sounder with the EMC Directive, does not confer compliance with the directive on any apparatus or systems connected to them.

Construction Products Regulation 305/2011/EU

The Ancillary Base Sounder complies with the essential requirements of the Construction Products Regulation 305/2011/EU.

A copy of the Declaration of Performance is available from the Apollo website: www.apollo-fire.co.uk

36 Brookside Road, Havant Hampshire, PO9 1JR, UK.

Tel: +44 (0)23 9249 2412 Fax: +44 (0)23 9249 2754 Email: sales@apollo-fire.com Web: www.apollo-fire.co.uk All information in this document is given in good faith but Apollo Fire Detectors Ltd cannot be held responsible for any omissions or errors. The company reserves the right to change the specifications of products at any time and without prior notice.









This page has intentionally been left blank

