



DATASHEET



BTEV

BT EVO 230V IP65 IK10 Adjustable Wattage and CCT LED Bulkhead

www.mlaccessories.co.uk



| MLA PART CODE | BTEV |
|-------------------------------|---|
| DESCRIPTION | BT EVO 230V IP65 IK10 Adjustable Wattage and CCT LED Bulkhead |
| NET WEIGHT (KG) | 0.8 |
| FINISH | White |
| DIFFUSER | Opal |
| DIMENSIONS (MM) | Diameter - 300 Projection - 65 |
| CONSTRUCTION | Construction - Polycarbonate |
| CLASS | II |
| IP RATING | IP65 |
| IK RATING | IK10 |
| WATTAGE (W) | 9/14/18 |
| LAMP TECHNOLOGY | SMD LED |
| LUMENS (LM) | 890/930/915,1295/1400/1330,1520/1750/1585 |
| LUMENS LIGHT SOURCE ONLY (LM) | 1215/1900/2300 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 136/136/134 |
| CIRCUIT WATTAGE (W) | 8.9/13.6/16.8 |
| CCT | 3000/4000/5700K |
| LIGHT COLOUR | CCT |
| CRI | >85 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.044/0.062/0.076 |
| DISPLACEMENT FACTOR | >0.7 |
| SVM | 0.05 |
| PST-LM | 0.15 |
| BEAM ANGLE (DEGREES) | 120 |
| L70B50 LIFESPAN (HRS) | 50,000 |
| DIMMABLE | No |

| | |
|--|--|
| OPERATING TEMPERATURE | -20~35°C |
| INPUT VOLTAGE | 230V 50Hz |
| DRIVER | DRIVER TYPE - Constant Current MAX. OUTPUT - 16.2W OUTPUT CURRENT - 360mA POWER FACTOR - 0.97 EFFICIENCY FULL LOAD - 0.87 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -20~50°C CASE TEMPERATURE (Tc) - 85°C |
| WARRANTY | 5year(s) |
| MANUFACTURED IN ACCORDANCE WITH | BS EN 60598 |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5056270852356 |

Date Created: 28/02/2025 01:18

