



## DATASHEET



### BATSCDAST4

230V 4ft 32W DALI CCT Adjustable Self-Test  
Emergency Batten

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)



MLA PART CODE	BATSCDAST4
DESCRIPTION	230V 4ft 32W DALI CCT Adjustable Self-Test Emergency Batten
NET WEIGHT (KG)	1.56
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1225 Width - 61 Projection - 71
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	I
IP RATING	IP20
WATTAGE (W)	32
LAMP TECHNOLOGY	LED
LUMENS (LM)	3790/4480/4120
LUMENS LIGHT SOURCE ONLY (LM)	4970
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	157.16
LUMENS EMERGENCY MODE (LM)	320
CIRCUIT WATTAGE (W)	31.66
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.141
DISPLACEMENT FACTOR	>0.9
SVM	0
PST-LM	0
BEAM ANGLE (DEGREES)	105
L70B50 LIFESPAN (HRS)	60,000

EMERGENCY	Maintained / Non-maintained / Switched
SELF-TEST	Yes
OPERATING TEMPERATURE	-5~40°C
INPUT VOLTAGE	230V 50Hz
CABLE GLAND INCLUDED	No
DRIVER	DRIVER TYPE - DALI MAX. OUTPUT - 31.5W OUTPUT VOLTAGE - 25-42V OUTPUT CURRENT - up to 750mA POWER FACTOR - 0.9 EFFICIENCY FULL LOAD - 95 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - 50°C CASE TEMPERATURE (Tc) - 90°C
BATTERY TYPE	LiFePO4
BATTERY INCLUDED	Yes
STANDBY POWER	≤ 0.5WW
WARRANTY	5year(s)
WARRANTY INFORMATION	(excluding battery)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270881738

Date Created: 27/02/2025 19:35

