



DATASHEET



TRLED15EM

230V IP65 5ft 29W Single LED Non-Corrosive Emergency

www.mlaccessories.co.uk



MLA PART CODE	TRLED15EM
DESCRIPTION	230V IP65 5ft 29W Single LED Non-Corrosive Emergency
NET WEIGHT (KG)	2.6
FINISH	Grey
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1563 Height - 90 Width - 94
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP65
WATTAGE (W)	29
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	3650
LUMENS LIGHT SOURCE ONLY (LM)	4040
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	145
LUMENS EMERGENCY MODE (LM)	844
CIRCUIT WATTAGE (W)	28.4
CCT	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.129
DISPLACEMENT FACTOR	>0.9
SVM	0.828
PST-LM	0.035
BEAM ANGLE (DEGREES)	120
LIFE SPAN (HRS)	25,000

L70B50 LIFESPAN (HRS)	50,000
DIMMABLE	No
EMERGENCY	Maintained / Non-maintained / Switched
OPERATING TEMPERATURE	-5~35°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 30W EFFICIENCY FULL LOAD - 89.11% ISOLATION - SELV
BATTERY TYPE	Ni-Cad
BATTERY INCLUDED	Yes
WARRANTY	5year(s)
WARRANTY INFORMATION	(excluding battery)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832971023

Date Created: 28/02/2025 22:23

