Xnightsbridge


DATASHEET



TRLEDA221

110V IP65 2ft 22W Twin LED Non-Corrosive

www.mlaccessories.co.uk



MLA PART CODE	TRLEDA221
DESCRIPTION	110V IP65 2ft 22W Twin LED Non-Corrosive
NET WEIGHT (KG)	1.22
FINISH	Yellow
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 653 Height - 90 Width - 129
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP65
WATTAGE (W)	22
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	2850
LUMENS LIGHT SOURCE ONLY (LM)	3310
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	155
CIRCUIT WATTAGE (W)	21.47
ССТ	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.0191
DISPLACEMENT FACTOR	>0.9
SVM	0.017
PST-LM	0.027
BEAM ANGLE (DEGREES)	130
L70B50 LIFESPAN (HRS)	50,000
LED COMPATIBLE	Yes





Xnightsbridge

DIMMABLE	No
OPERATING TEMPERATURE	-20~35°C
INPUT VOLTAGE	110/230V
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
DRIVER	DRIVER TYPE - Constant Current
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270856507

Date Created: 28/02/2025 00:59





