Xnightsbridge

DATASHEET



CS9940BCW

13A 2G SP Switched Socket with Dual USB A+C (5V DC 4.0A shared) - Brushed Chrome with White Insert

www.mlaccessories.co.uk

NET WEIGHT (KG) 0.271	MLA PART CODE	CS9940BCW
FINISH NSERT COLOUR White Height - 89 Width - 149.3 Depth - 29.1 Projection - 15.6 Recessed Depth - 13.5 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION P RATING IP20 NPUT VOLTAGE SWITCH TYPE Single Pole EARTH TERMINAL OAD/MAX. LOAD 13A TERMINAL CAPACITY 10. OF USB PORTS 10. OF TYPE-A PORTS 11. ON OF TYPE-C PORTS 12. OR TYPE-C PORTS 13. OR TYPE-C PORTS 14. OR TYPE-C PORTS 15. OR TYPE-C PORTS 16. OR TYPE-C PORTS 17. OR TYPE-C PORTS 18. OR TYPE-C PORTS 19. OR TYPE-C PORTS 19. OR TYPE-C PORTS 29. OR TYPE-C PORTS 10. OR TYPE-C PORTS 10. OR TYPE-C PORTS 10. OR TYPE-C PORTS 10. OR TYPE-C PORTS 11. OR TYPE-C PORTS 12. OR TYPE-C PORTS 13. OR TYPE-C PORTS 14. OR TYPE-C PORTS 15. OR TYPE-C PORTS 16. OR TYPE-C PORTS 17. OR TYPE-C PORTS 18. OR TYPE-C PORTS 19. OR TYPE-C PORTS	DESCRIPTION	13A 2G SP Switched Socket with Dual USB A+C (5V DC 4.0A shared) - Brushed Chrome with White Insert
NEERT COLOUR White	NET WEIGHT (KG)	0.271
Height - 89 Width - 149.3 Depth - 29.1 Projection - 15.6 Recessed Depth - 13.5	FINISH	Brushed Chrome
DIMENSIONS (MM) Depth - 29.1 Projection - 15.6 Recessed Depth - 13.5	INSERT COLOUR	White
CONSTRUCTION Construction - 430 Stainless Steel CLASS I P RATING IP20 NPUT VOLTAGE 230V 50Hz SWITCH TYPE Single Pole EARTH TERMINAL Yes LOAD/MAX. LOAD 13A TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 1 NO. OF TYPE-C PORTS 1 USB CHARGING 5V DC 4.0A (shared) WARRANTY 2year(s) ORIGIN OF MANUFACTURE China	DIMENSIONS (MM)	Width - 149.3 Depth - 29.1 Projection - 15.6
CLASS	MINIMUM MOUNTING BOX DEPTH	25mm
PRATING NPUT VOLTAGE SWITCH TYPE Single Pole EARTH TERMINAL OAD/MAX. LOAD TERMINAL CAPACITY NO. OF USB PORTS NO. OF TYPE-A PORTS NO. OF TYPE-C PORTS 1 JSB CHARGING WARRANTY DRIGIN OF MANUFACTURE 1 1 1 1 1 1 1 1 1 1 1 1 1	CONSTRUCTION	Construction - 430 Stainless Steel
NPUT VOLTAGE 230V 50Hz SWITCH TYPE Single Pole EARTH TERMINAL Yes LOAD/MAX. LOAD 13A TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 1 NO. OF TYPE-C PORTS 1 JSB CHARGING 5V DC 4.0A (shared) WARRANTY 2year(s) DRIGIN OF MANUFACTURE China	CLASS	I
SWITCH TYPE Single Pole EARTH TERMINAL Yes LOAD/MAX. LOAD 13A TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 1 NO. OF TYPE-C PORTS 1 USB CHARGING 5V DC 4.0A (shared) WARRANTY 2year(s) DRIGIN OF MANUFACTURE China	IP RATING	IP20
Yes	INPUT VOLTAGE	230V 50Hz
LOAD/MAX. LOAD 13A FERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 1 NO. OF TYPE-C PORTS 1 USB CHARGING 5V DC 4.0A (shared) WARRANTY 2year(s) ORIGIN OF MANUFACTURE China	SWITCH TYPE	Single Pole
TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm² NO. OF USB PORTS 2 NO. OF TYPE-A PORTS 1 NO. OF TYPE-C PORTS 1 JSB CHARGING 5V DC 4.0A (shared) WARRANTY 2year(s) DRIGIN OF MANUFACTURE China	EARTH TERMINAL	Yes
NO. OF USB PORTS NO. OF TYPE-A PORTS 1 NO. OF TYPE-C PORTS 1 JSB CHARGING VARRANTY 2 Zyear(s) China	LOAD/MAX. LOAD	13A
NO. OF TYPE-A PORTS 1 NO. OF TYPE-C PORTS 1 JSB CHARGING VARRANTY 2year(s) China	TERMINAL CAPACITY	2 x 2.5mm² or 1 x 4.0mm²
NO. OF TYPE-C PORTS JSB CHARGING WARRANTY DRIGIN OF MANUFACTURE 1 5V DC 4.0A (shared) 2year(s) China	NO. OF USB PORTS	2
JSB CHARGING 5V DC 4.0A (shared) WARRANTY 2year(s) DRIGIN OF MANUFACTURE China	NO. OF TYPE-A PORTS	1
NARRANTY 2year(s) DRIGIN OF MANUFACTURE China	NO. OF TYPE-C PORTS	1
DRIGIN OF MANUFACTURE China	USB CHARGING	5V DC 4.0A (shared)
	WARRANTY	2year(s)
DECLARATION OF CONFORMITY (HELD ON FILE)	ORIGIN OF MANUFACTURE	China
res	DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN 5056270885392	EAN	5056270885392

Date Created: 27/02/2025 20:00



