

DATASHEET



EMSWING

230V IP20 Ceiling Mounted LED Emergency Exit Sign (maintained/non-maintained)

www.mlaccessories.co.uk

MLA PART CODE	EMSWING
DESCRIPTION	230V IP20 Ceiling Mounted LED Emergency Exit Sign (maintained/non-maintained)
NET WEIGHT (KG)	1.19
FINISH	Brushed Chrome
DIMENSIONS (MM)	Length - 332 Height - 222 Width - 25 Base Width - 330 Base Height - 30 Base Depth - 36 Overall Height - 1500
CONSTRUCTION	Construction - Aluminium
CLASS	I
IP RATING	IP20
WATTAGE (W)	4
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	70
EFFICACY (LM/W)	20
LUMENS EMERGENCY MODE (LM)	34
CIRCUIT WATTAGE (W)	4.3
CCT	6000K
LIGHT COLOUR	Daylight
CRI	>70
RUNNING CURRENT (A)	0.04
BEAM ANGLE (DEGREES)	120
LIFE SPAN (HRS)	40,000
DIMMABLE	No
EMERGENCY	Maintained / Non-maintained / Switched
SELF-TEST	No
OPERATING TEMPERATURE	0~45°C

INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	1.25
CABLE TYPE	H03VV-F 4 x 0.5
BATTERY TYPE	Ni-Cad
BATTERY INCLUDED	Yes
WARRANTY	3year(s)
WARRANTY INFORMATION	(excluding battery)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598-2-22
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055559180029

Date Created: 27/02/2025 10:42

