## **X**nightsbridge

## **DATASHEET**



## FP82MNBB

45A DP Switch with Neon (2G size) - Brushed Brass

www.mlaccessories.co.uk

STATE   STAT	MLA PART CODE	FP82MNBB
Brushed Brass  Height - 147.5 Width - 87.5 Depth - 29.8 Projection - 7.5 Recessed Depth - 22.3  MINIMUM MOUNTING BOX DEPTH  CONSTRUCTION  CONSTRUCTION CONSTRUCTION - 201 Stainless steel  I PRATING  IP20  NPUT VOLTAGE  CONSTRUCT  PRATING  IP20  NPUT VOLTAGE  CONSTRUCT  PROVIDED  PRATING  IP20  NPUT VOLTAGE  CONSTRUCT  PROVIDED  CONSTRUCT  IP20  PRATING  IP20  PRATING  IP20  PRATING  IP20  PROVIDED  CONSTRUCT  IP20  PRATING  IP20  IP20  PRATING  IP20  IP20  PRATING  IP20  IP	DESCRIPTION	45A DP Switch with Neon (2G size) - Brushed Brass
Height - 147.5 Width - 87.5 Depth - 29.8 Projection - 7.5 Recessed Depth - 22.3  MINIMUM MOUNTING BOX DEPTH  CONSTRUCTION  IP20	NET WEIGHT (KG)	0.175
DIMENSIONS (MM)  Dimensions (MM)  Dipth - 29.8 Projection - 7.5 Recessed Depth - 22.3  DIMINIMUM MOUNTING BOX DEPTH  CONSTRUCTION  Construction - 201 Stainless steel  CLASS  I PRATING  IP20  NPUT VOLTAGE  SWITCH TYPE  Double Pole  EARTH TERMINAL  Yes JEON INDICATOR  JEON INDICATOR  CONSTRUCTION  Yes  JEON INDICATOR  ASA  JERMINAL CAPACITY	FINISH	Brushed Brass
CONSTRUCTION CONST	DIMENSIONS (MM)	Width - 87.5 Depth - 29.8 Projection - 7.5
I	MINIMUM MOUNTING BOX DEPTH	47mm
PRATING  NPUT VOLTAGE  SWITCH TYPE  Double Pole  EARTH TERMINAL  Yes  NEON INDICATOR  Yes  OAD/MAX. LOAD  TERMINAL CAPACITY  VARRANTY  VARRANTY  MANUFACTURED IN ACCORDANCE WITH  DECLARATION OF CONFORMITY (HELD ON FILE)  PRATING  1P20  1P20  230V 50Hz  Double Pole  Yes  45A  2 x 6.0mm² or 3 x 4.0mm²  2 yes  China  Yes	CONSTRUCTION	Construction - 201 Stainless steel
NPUT VOLTAGE  SWITCH TYPE  Double Pole  EARTH TERMINAL  YES  JEON INDICATOR  YES  JOAD/MAX. LOAD  TERMINAL CAPACITY  VARRANTY  VARRANTY  MANUFACTURED IN ACCORDANCE WITH  DECLARATION OF CONFORMITY (HELD ON FILE)  230V 50Hz  Double Pole  Yes  240 Manufacture  Double Pole  Yes  250 Manufacture  China  Yes	CLASS	I
EARTH TERMINAL Yes  IEON INDICATOR Yes  OAD/MAX. LOAD  TERMINAL CAPACITY YARRANTY YARRANTY YARRANTY YES  MANUFACTURED IN ACCORDANCE WITH DECLARATION OF CONFORMITY (HELD ON FILE)  DOUBle Pole Yes  Yes  1	IP RATING	IP20
EARTH TERMINAL SECON INDICATOR SECON INDICATOR SECON INDICATOR SECON INDICATOR Yes	INPUT VOLTAGE	230V 50Hz
ALCON INDICATOR  ADDITION OF CONFORMITY (HELD ON FILE)  Yes  45A  2 x 6.0mm² or 3 x 4.0mm²  2 x	SWITCH TYPE	Double Pole
ADDITION OF CONFORMITY (HELD ON FILE)  45A  2 x 6.0mm² or 3 x 4.0mm²	EARTH TERMINAL	Yes
TERMINAL CAPACITY  2 x 6.0mm² or 3 x 4.0mm²  25year(s)  MANUFACTURED IN ACCORDANCE WITH  DRIGIN OF MANUFACTURE  China  DECLARATION OF CONFORMITY (HELD ON FILE)  Yes	NEON INDICATOR	Yes
VARRANTY  25year(s)  MANUFACTURED IN ACCORDANCE WITH  DRIGIN OF MANUFACTURE  DECLARATION OF CONFORMITY (HELD ON FILE)  Yes	LOAD/MAX. LOAD	45A
MANUFACTURED IN ACCORDANCE WITH  DRIGIN OF MANUFACTURE  DECLARATION OF CONFORMITY (HELD ON FILE)  Yes	TERMINAL CAPACITY	2 x 6.0mm <sup>2</sup> or 3 x 4.0mm <sup>2</sup>
DRIGIN OF MANUFACTURE China DECLARATION OF CONFORMITY (HELD ON FILE) Yes	WARRANTY	25year(s)
DECLARATION OF CONFORMITY (HELD ON FILE)  Yes	MANUFACTURED IN ACCORDANCE WITH	BS EN 60669-1
	ORIGIN OF MANUFACTURE	China
F0F077047701	DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
SAN 5056270847031	EAN	5056270847031

Date Created: 27/02/2025 19:13





