## **X**nightsbridge

## **DATASHEET**



## SFR9940BN

13A 2G SP Switched Socket with Dual USB A+C (5V DC 4.0A shared) - Black Nickel with Black Insert

www.mlaccessories.co.uk

Shared   - Black Nickel With Black Insert	MLA PART CODE	SFR9940BN
Black Nickel  NSERT COLOUR  Black  Height - 87.5 Width - 147.5 Depth - 34.5 Projection - 9.3 Recessed Depth - 25.2  MINIMUM MOUNTING BOX DEPTH  CONSTRUCTION  CONSTRUCTION	DESCRIPTION	13A 2G SP Switched Socket with Dual USB A+C (5V DC 4.0A shared) - Black Nickel with Black Insert
Black	NET WEIGHT (KG)	0.285
Height - 87.5   Width - 147.5   Depth - 34.5   Projection - 9.3   Recessed Depth - 25.2	FINISH	Black Nickel
DIMENSIONS (MM)  DIMENSIONS (MM)  DIMENSIONS (MM)  DIMENSIONS (MM)  DIMENSIONS (MM)  DIP H - 147.5 Depth - 34.5 Projection - 9.3 Recessed Depth - 25.2  DIMINIMUM MOUNTING BOX DEPTH  DESCRIPTION  DESCRIPTION  Construction - 201 Stainless steel  CLASS  I PRATING  IP20  NPUT VOLTAGE  DESCRIPTION  DISTRICT TYPE  Single Pole  DESCRIPTION  DESCRIP	INSERT COLOUR	Black
CONSTRUCTION         Construction - 201 Stainless steel           CLASS         I           P RATING         IP20           NPUT VOLTAGE         230V 50Hz           SWITCH TYPE         Single Pole           CARTH TERMINAL         Yes           COAD/MAX. LOAD         13A           TERMINAL CAPACITY         2 x 2.5mm² or 1 x 4.0mm²           MO. OF USB PORTS         2           MO. OF TYPE-A PORTS         1           MO. OF TYPE-C PORTS         1           MOS CHARGING         5V DC 4.0A (shared)           VARRANTY         2year(s)	DIMENSIONS (MM)	Width - 147.5 Depth - 34.5 Projection - 9.3
I   I   I   I   I   I   I   I   I   I	MINIMUM MOUNTING BOX DEPTH	25-35mm (dependent on wiring conditions)
PRATING	CONSTRUCTION	Construction - 201 Stainless steel
NPUT VOLTAGE   230V 50Hz	CLASS	I
SWITCH TYPE         Single Pole           EARTH TERMINAL         Yes           .OAD/MAX. LOAD         13A           TERMINAL CAPACITY         2 x 2.5mm² or 1 x 4.0mm²           NO. OF USB PORTS         2           NO. OF TYPE-A PORTS         1           NO. OF TYPE-C PORTS         1           USB CHARGING         5V DC 4.0A (shared)           VARRANTY         2year(s)	IP RATING	IP20
EARTH TERMINAL       Yes         .OAD/MAX. LOAD       13A         TERMINAL CAPACITY       2 x 2.5mm² or 1 x 4.0mm²         NO. OF USB PORTS       2         NO. OF TYPE-A PORTS       1         NO. OF TYPE-C PORTS       1         JSB CHARGING       5V DC 4.0A (shared)         VARRANTY       2year(s)	INPUT VOLTAGE	230V 50Hz
OAD/MAX. LOAD       13A         TERMINAL CAPACITY       2 x 2.5mm² or 1 x 4.0mm²         NO. OF USB PORTS       2         NO. OF TYPE-A PORTS       1         NO. OF TYPE-C PORTS       1         USB CHARGING       5V DC 4.0A (shared)         VARRANTY       2year(s)	SWITCH TYPE	Single Pole
TERMINAL CAPACITY         2 x 2.5mm² or 1 x 4.0mm²           NO. OF USB PORTS         2           NO. OF TYPE-A PORTS         1           NO. OF TYPE-C PORTS         1           USB CHARGING         5V DC 4.0A (shared)           VARRANTY         2year(s)	EARTH TERMINAL	Yes
NO. OF USB PORTS  10. OF TYPE-A PORTS  1 TO TYPE-C PORTS  1 SYDC 4.0A (shared)  VARRANTY  2 Year(s)	LOAD/MAX. LOAD	13A
NO. OF TYPE-A PORTS  1 NO. OF TYPE-C PORTS  1 USB CHARGING  5V DC 4.0A (shared)  2year(s)	TERMINAL CAPACITY	2 x 2.5mm² or 1 x 4.0mm²
IO. OF TYPE-C PORTS  JSB CHARGING  VARRANTY  1  5V DC 4.0A (shared)  2year(s)	NO. OF USB PORTS	2
JSB CHARGING 5V DC 4.0A (shared) VARRANTY 2year(s)	NO. OF TYPE-A PORTS	1
VARRANTY 2year(s)	NO. OF TYPE-C PORTS	1
	USB CHARGING	5V DC 4.0A (shared)
	WARRANTY	2year(s)
DRIGIN OF MANUFACTURE China	ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE) Yes	DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN 5056270835250	EAN	5056270835250

Date Created: 28/02/2025 00:35



