



DATASHEET



SER712AD

SEREN 230V IP40 LED Recessed Tri-Wattage and CCT 0-10V Downlight - 7/ 10/ 12W

www.mlaccessories.co.uk



| MLA PART CODE | SER712AD |
|-------------------------------|---|
| DESCRIPTION | SEREN 230V IP40 LED Recessed Tri-Wattage and CCT 0-10V Downlight - 7/ 10/ 12W |
| NET WEIGHT (KG) | 0.65 |
| FINISH | White |
| DIFFUSER | Opal |
| DIMENSIONS (MM) | Diameter - 143 Recessed Depth - 69.5 Minimum Void - 100 |
| CUT-OUT (MM) | Cut-out Diameter - 125 |
| CONSTRUCTION | Construction - Aluminium Construction 2 - & polycarbonate |
| CLASS | II |
| IP RATING | IP40 (IP20 from above) |
| WATTAGE (W) | 7 / 10 / 12 |
| LAMP TECHNOLOGY | SMD LED |
| LAMP INCLUDED | Yes |
| LUMENS (LM) | 950/995/1000/1290/1360/1350/1490/1575/1575 |
| LUMENS LIGHT SOURCE ONLY (LM) | 1810 |
| LUMEN TOLERANCE | 10% |
| EFFICACY (LM/W) | 155 |
| CIRCUIT WATTAGE (W) | 11.88 |
| CCT | 3000/4000/5000K |
| LIGHT COLOUR | CCT |
| CRI | >80 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.054 |
| DISPLACEMENT FACTOR | >0.9 |
| SVM | 0.007 |
| PST-LM | 0.59 |
| BEAM ANGLE (DEGREES) | 100 |

| | |
|--|---------------|
| L70B50 LIFESPAN (HRS) | 50,000 |
| LED COMPATIBLE | Yes |
| DIMMABLE | Yes* |
| EMERGENCY CONVERSION KIT | EMKIT2L |
| IC RATED | No |
| OPERATING TEMPERATURE | -25~45°C |
| INPUT VOLTAGE | 230V 50Hz |
| WARRANTY | 5year(s) |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5056270843859 |

Date Created: 28/02/2025 00:54

