Xnightsbridge

DATASHEET



SF2193AT

3G 2-way 10-200W (5-150W LED) Intelligent dimmer - Anthracite

www.mlaccessories.co.uk

DESCRIPTION3G 2-way 10-200W (5-150W LED) Intelligent dimmer - AnthraciteNET WEIGHT (KG)0.337FINISHAnthraciteDIMENSIONS (MM)Height - 87.5 Width - 147.5 Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3MINIMUM MOUNTING BOX DEPTH25mmCONSTRUCTIONConstruction - SPCC SteelCLASSIIP RATINGIP20INPUT VOLTAGE230V 50Hz	
FINISH Anthracite Height - 87.5 Width - 147.5 Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION IP RATING IP20 INPUT VOLTAGE	
DIMENSIONS (MM) Height - 87.5 Width - 147.5 Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3 MINIMUM MOUNTING BOX DEPTH 25mm CONSTRUCTION Construction - SPCC Steel CLASS I IP RATING IP20 INPUT VOLTAGE 230V 50Hz	
DIMENSIONS (MM) Width - 147.5 Depth - 43.9 Projection - 22.6 Recessed Depth - 21.3 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION Construction - SPCC Steel CLASS I IP RATING IP20 INPUT VOLTAGE 230V 50Hz	
CONSTRUCTION Construction - SPCC Steel CLASS I IP RATING IP20 INPUT VOLTAGE 230V 50Hz	
CLASS I IP RATING IP20 INPUT VOLTAGE 230V 50Hz	
IP RATING IP20 INPUT VOLTAGE 230V 50Hz	
INPUT VOLTAGE 230V 50Hz	
SWITCH FUNCTION 2-Way	
EARTH TERMINAL Yes	
LOAD/MAX. LOAD 10-200W (5-150W LED) Max. 15 Lamps per dimmer	
TERMINAL TYPE Screw	
TERMINAL CAPACITY 2 x 1.0mm² or 2 x 1.5mm²	
BUILT-IN TECHNOLOGY Intelligent - Switchable Leading Edge and Trailing Edge (de	fault)
ADDITIONAL FEATURES Trim, switch modes and reset dimmer all from the front of plate via the control knob	the
WARRANTY 2year(s)	
ORIGIN OF MANUFACTURE China	
DECLARATION OF CONFORMITY (HELD ON FILE) Yes	
EAN 5056270835373	

Date Created: 28/02/2025 00:37



