Xnightsbridge

DATASHEET




TNXTMWEM

TENAX 230V Wattage and CCT Adjustable Emergency LED Gear Tray with Sensor

www.mlaccessories.co.uk





MLA PART CODE	TNXTMWEM
DESCRIPTION	TENAX 230V Wattage and CCT Adjustable Emergency LED Gear Tray with Sensor
NET WEIGHT (KG)	0.351
DIMENSIONS (MM)	Length - 235 Width - 235 Projection - 28
CONSTRUCTION	Construction - Aluminium
CLASS	II
IP RATING	IP20
WATTAGE (W)	10/15/20
LAMP TECHNOLOGY	SMD LED
LUMENS (LM)	1360/1480/1405, 1905/2090/1960, 2345/2630/2415
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	151/147/141
LUMENS EMERGENCY MODE (LM)	125
CIRCUIT WATTAGE (W)	9.7/14.3/18.6
ССТ	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.049/0.067/0.085
DISPLACEMENT FACTOR	>0.7
SVM	0.69
PST-LM	0.36
BEAM ANGLE (DEGREES)	120
L70B50 LIFESPAN (HRS)	40,000
DIMMABLE	No
EMERGENCY	Maintained / Non-maintained / Switched
SELF-TEST	No





Xnightsbridge

OPERATING TEMPERATURE	-5~35°C
INPUT VOLTAGE	230V 50Hz
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 18W OUTPUT CURRENT - 360mA POWER FACTOR - 0.96 EFFICIENCY FULL LOAD - 0.89 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C CASE TEMPERATURE (Tc) - 85°C
SENSOR TYPE	Microwave
SENSOR OVERRIDE	No
SENSOR DETECTION ANGLE (DEGREES)	150
OPTIMUM DETECTION RANGE (M)	3-5m (mounting height 3m)
SENSOR DURATION	5 seconds - 30 minutes
BATTERY TYPE	LiFePO4
SENSOR LUX SETTINGS	2 lux - 50 lux / Disable
BATTERY INCLUDED	Yes
WARRANTY	5year(s)
WARRANTY INFORMATION	including battery
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270894745

Date Created: 27/02/2025 20:07





