Xnightsbridge

DATASHEET



FPR9940PB

13A 2G SP Switched Socket with Dual USB A+C (5V DC 4.0A shared) - Polished Brass with Black Insert

www.mlaccessories.co.uk

DESCRIPTION 13A 2G SP Switched Socket with Dual USB A+C (5V DC 4.0 shared) - Polished Brass with Black Insert 0.213 FINISH Polished Brass INSERT COLOUR Black Height - 87.5 Width - 147.5 Depth - 34.5 Projection - 7.5 Recessed Depth - 27 MINIMUM MOUNTING BOX DEPTH 25-35mm (dependent on wiring conditions) CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION IP20 INPUT VOLTAGE SWITCH TYPE Single Pole EARTH TERMINAL		FPR9940PB
FINISH INSERT COLOUR Black Height - 87.5 Width - 147.5 Depth - 34.5 Projection - 7.5 Recessed Depth - 27 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION CONSTR	1	G SP Switched Socket with Dual USB A+C (5V DC 4.0A shared) - Polished Brass with Black Insert
INSERT COLOUR Black Height - 87.5 Width - 147.5 Depth - 34.5 Projection - 7.5 Recessed Depth - 27 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION IP RATING IP20 INPUT VOLTAGE SWITCH TYPE Single Pole		0.213
Height - 87.5 Width - 147.5 Depth - 34.5 Projection - 7.5 Recessed Depth - 27 MINIMUM MOUNTING BOX DEPTH 25-35mm (dependent on wiring conditions) CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION IP RATING IP20 INPUT VOLTAGE SWITCH TYPE Single Pole		Polished Brass
MINIMUM MOUNTING BOX DEPTH CONSTRUCTION CLASS IP PATING IP PATING INPUT VOLTAGE SWITCH TYPE Width - 147.5 Depth - 34.5 Projection - 7.5 Recessed Depth - 27 25-35mm (dependent on wiring conditions) Construction - 201 Stainless steel I P20 Single Pole		Black
CONSTRUCTION CLASS I IP RATING INPUT VOLTAGE SWITCH TYPE Construction - 201 Stainless steel I Single Pole		Width - 147.5 Depth - 34.5 Projection - 7.5
CLASS I I IP RATING IP20 INPUT VOLTAGE 230V 50Hz SWITCH TYPE Single Pole	BOX DEPTH	25-35mm (dependent on wiring conditions)
IP RATING IP20 INPUT VOLTAGE 230V 50Hz SWITCH TYPE Single Pole		Construction - 201 Stainless steel
INPUT VOLTAGE 230V 50Hz SWITCH TYPE Single Pole		I
SWITCH TYPE Single Pole		IP20
		230V 50Hz
EARTH TERMINAL Yes		Single Pole
		Yes
LOAD/MAX. LOAD 13A		13A
TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm²		2 x 2.5mm² or 1 x 4.0mm²
NO. OF USB PORTS 2		2
NO. OF TYPE-A PORTS 1	S	1
NO. OF TYPE-C PORTS 1	S	1
USB CHARGING 5V DC 4.0A (shared)		5V DC 4.0A (shared)
WARRANTY 2year(s)		2year(s)
ORIGIN OF MANUFACTURE China	TURE	China
DECLARATION OF CONFORMITY (HELD ON FILE) Yes	NFORMITY (HELD ON FILE)	Yes
EAN 5056270883671		5056270883671

Date Created: 27/02/2025 19:59



