



## DATASHEET



### LUMI6060

230V IP40 600mm x 600mm 4000K 30W LED Backlit Panel

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)



MLA PART CODE	LUMI6060
DESCRIPTION	230V IP40 600mm x 600mm 4000K 30W LED Backlit Panel
NET WEIGHT (KG)	1.4
FINISH	White
DIFFUSER	Prismatic
DIMENSIONS (MM)	Length - 595 Height - 25 Width - 595 Projection - 9
CONSTRUCTION	Construction - Aluminium
CLASS	II
IP RATING	IP40
WATTAGE (W)	30
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	4385
LUMENS LIGHT SOURCE ONLY (LM)	4830
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	175
CIRCUIT WATTAGE (W)	27.9
CCT	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.13
DISPLACEMENT FACTOR	>0.9
SVM	0.01
PST-LM	0.01
BEAM ANGLE (DEGREES)	110
L70B50 LIFESPAN (HRS)	50000

DIMMABLE	No
EMERGENCY CONVERSION KIT	EMKIT2L
IC RATED	No
DIFFUSER RATING	TP(a)
OPERATING TEMPERATURE	-10~40°C
INPUT VOLTAGE	230V 50Hz
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 32W OUTPUT VOLTAGE - 33-40V OUTPUT CURRENT - 800mA POWER FACTOR - 0.9 EFFICIENCY FULL LOAD - 87 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - 45°C CASE TEMPERATURE (Tc) - 90°C
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270859065

Date Created: 27/02/2025 19:42

