## **X**nightsbridge

## **DATASHEET**



## SFR9NLBCG

13A 2G DP Switched Socket with Photocell Nightlight Function - Brushed Chrome with Grey Insert

www.mlaccessories.co.uk

MLA PART CODE	SFR9NLBCG
DESCRIPTION	13A 2G DP Switched Socket with Photocell Nightlight Function - Brushed Chrome with Grey Insert
NET WEIGHT (KG)	0.282
FINISH	Brushed Chrome
INSERT COLOUR	Grey
DIMENSIONS (MM)	Height - 87.5 Width - 147.5 Depth - 35.6 Projection - 12.2 Recessed Depth - 23.4
MINIMUM MOUNTING BOX DEPTH	25-35mm (dependent on wiring conditions)
CONSTRUCTION	Construction - 201 Stainless steel
CLASS	I
IP RATING	IP20
WATTAGE (W)	0.8
LAMP TECHNOLOGY	LED
LUMENS (LM)	55
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	73.1
ССТ	4000K
CRI	>85
RUNNING CURRENT (A)	0.01
INPUT VOLTAGE	230V 50Hz
SWITCH TYPE	Double Pole
EARTH TERMINAL	Yes
LOAD/MAX. LOAD	13A
TERMINAL CAPACITY	3 x 2.5mm² or 2 x 4.0mm²
ADDITIONAL FEATURES	Built in Night Light
SENSOR TYPE	Photocell
SENSOR OVERRIDE	No





## **X**nightsbridge

SENSOR LUX SETTINGS	On 5-15 lux, off 20-40 lux, non-adjustable
WARRANTY	2year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598, BS EN 62493, BS 1363-2
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270869958

Date Created: 27/02/2025 19:45





