



DATASHEET



AS30CWA

ASHA 230V 30W IP54 CCT Adjustable LED Downlight

www.mlaccessories.co.uk



MLA PART CODE	AS30CWA
DESCRIPTION	ASHA 230V 30W IP54 CCT Adjustable LED Downlight
NET WEIGHT (KG)	0.87
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 235 Base Diameter - 197 Recessed Depth - 46 Minimum Void - 96
CUT-OUT (MM)	Cut-out Diameter - 205
CONSTRUCTION	Construction - Polycarbonate Construction 2 - & aluminium
CLASS	II
IP RATING	IP54 (IP20 from above)
WATTAGE (W)	30
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	3400/3695/3600
LUMENS LIGHT SOURCE ONLY (LM)	3405/3805/3635
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	125
CIRCUIT WATTAGE (W)	30.5
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.1359
DISPLACEMENT FACTOR	>0.9
SVM	0.005
PST-LM	0.01
BEAM ANGLE (DEGREES)	100

LIFE SPAN (HRS)	50,000
L70B50 LIFESPAN (HRS)	45000
LED COMPATIBLE	Yes
DIMMABLE	No
EMERGENCY CONVERSION KIT	EMKIT2L
IC RATED	No
OPERATING TEMPERATURE	-20~40°C
INPUT VOLTAGE	230V 50Hz
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 30.23W OUTPUT VOLTAGE - 40V OUTPUT CURRENT - 755mA EFFICIENCY FULL LOAD - 89.20
WARRANTY	3year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270844351

Date Created: 28/02/2025 01:01

