



# TOUCH FREE EXIT DEVICE

## HELPS STOP THE SPREAD OF GERMS

**EXIT BUTTONS**

Market leading request to exit buttons, that are both hard wearing and cost effective. Suitable for use in applications where contactless options are a priority.



**EBNT/TF-4**



**Anti Bacterial Plastic**



**EBNT/TF-5**

### SPECIFICATION

#### EBNT/TF-4 & 5

- Contacts: Double pole NONC contacts
- Contact Load: 0.5A @ AC 125V / 2A @ DC30V
- Voltage: 12 VDC @ 45mA operating
- +/- 10% voltage tolerance
- Legend: No Touch Exit
- Button rated IP65 ingress protection
- Relay timer: 5 seconds
- Operating distance: 0-150mm
- -30° to +80° operating temperature
- Humidity: 20%-80%
- Designed to prevent interference with other infra red devices

Requires a permanent power supply  
- volt free contacts

### DIMENSIONS

#### EBNT/TF-4

- 85x85x32 (mm)
- 140g (Boxed)
- 106g (Unboxed)

#### EBNT/TF-5

- 85x85x32 (mm)
- 220g (Boxed)
- 184g (Unboxed)

### FEATURES

#### EBNT/TF-4 & 5

- 35mm Touch free sensor button
- Illumination - Red for standby, Green for switch operated/door open
- Manufactured using anti bacterial materials
- High impact plastic back box
- Can be surface or flush fitting
- Easy clean surface
- Ideal for general / sensitive areas
- Screw footprint for flush fitting onto standard back box
- Distance between fixing holes 60mm

#### Suitable Alternative Back Boxes

- EXTR02 (Aluminium Extrusion 40mm)
- SSBB02 (Stainless Steel Back Box 42mm)
- PBB05 (Green or Black Back Box 40mm)

### CONTENTS

#### EBNT/TF-4 & 5

- Touch free button
- Back box
- Screw bag
- Instructions

### OTHER PRODUCTS

**1201SM-1**



**RD26-C**



**ML600**



**DU-NT/TF**



Manufactured by a BSIA Member